SPECIFICATION





TECHNICAL DATA LOA **HULL LENGTH** LWL BEAM DRAUGHT standard competition shallow keel 2.03 m / 6' 8" 2.24 m / 7' 5" 1.60 m / 5' 3" BALLAST 2.38 t / 5,247 lbs 2.05 t / 4,508 lbs 2.75 t / 6,062 lbs DISPLACEMENT 7.50 t / 16,534 lbs 7.00 t / 15,432 lbs 7.60 t / 16,755 lbs standard competition shallow keel **ENGINE APPROX.** FRESH WATER approx. 295 I / 77.93 gal approx. 160 l / 42.27 gal **FUEL TANK** MAST ABOVE WL standard & alu carbon 17.70 m / 58' 1'' 17.80 m / 58' 5'' **TOTAL SAIL AREA** competition alu 84.50 m² / 910 sq ft 85.25 m² / 918 sq ft MAIN SAIL standard 42.80 m² / 461 sq ft 49.40 m² / 532 sq ft 49.34 m² / 531 sq ft competition alu competition carbon 35.10 m² / 378 sq ft 35.10 m² / 378 sq ft 35.91 m² / 387 sq ft competition alu competition carbon SPINNAKER competition **GENNAKER** 103.70 m² / 1,116 sq ft 121.00 m² / 1,302 sq ft **FREERIDE** RIG I 15.07 m / 49' 5'' J 4.36 m / 14' 4" P 14.50 m / 47' 7" **CE CERTIFICATE** DESIGN

INTERIOR

All measurements/figures are approximate. Errors and omissions excepted. Specification and material can be changed without notice. Valid for deliveries from 2025.01.01 until 2025.06.30. D19A.24.V.2023-11-28.441


DECK AND INTERIOR LAYOUTS Dehler 3850




DECK LAYOUT




INTERIOR LAYOUT







OPTION



STANDARD SPECIFICATION



HULL

- 6 hull windows (3 each side)
- GRP hull, isophthalic gelcoat, colour Signal White (similar RAL 9003), 1st layer vinyl ester resin and balsa sandwich laminat
- Waterline and cove line, isophthalic gelcoat, colour: Dark Blue (similar RAL 5004)

KEEL

- L-keel, cast iron, standard draft: 2.03 m
- GRP rudder with sea-water resistant aluminium shaft and selfaligning bearings

LAYOUT & INTERIOR

- A1: Master cabin with double V-berth, hanging locker and shelves
- B1: Saloon with L-galley, dining area on stb and long sofa on port - separate head on port with "Dehler Uni Door System" to shower stall
- C1: Aft cabin with double berth, locker and storage on stb, large storage space on port with entrance from head
- 2-burner gas stove, waste bin, 12 V fridge approx. 130 I, double stainless steel sink with mixing tab
- Interior furniture in high quality marine plywood, satin varnish
- Dehler companionway closing system
- Saloon table, folding with stowage
- Worktop in galley, Off White
- SLS Scenario light system touch screen controller with dimmer for saloon

WOOD (FURNITURE, FLOORBOARD)

- Furniture Mahogany
- Floorboard Australian Acacia

UPHOLSTERY

- Mattrasses for all berths
- Upholstery Baltic, colour: creme
- Upholstery Piping (colour selection)

DECK & OUTSIDE EQUIPMENT

- GRP deck with antslip surface, isophthalic gelcoat, coulour: Signal White (similar RAL 9003), 1st layer vinyl ester resin with balsa sandwich core. Cockpit locker on port, stern locker on port and stb, anchor locker at bow.
- Synthetic teak on cockpit benches (colour selection)
- Twin wheel steering system with emergency tiller
- 2 stainless steel steering wheels with leather cover
- Pulpit and pushpit, stainless steel
- Railing, incl. stanchions and stainless steel wire
- Halyards and control lines with organizers and jammers on coachroof, 4 retractable mooring cleats, handrail on coach roof
- 2 LEWMAR 40 Race manual halyard winches
- 2 LEWMAR 45 Race manual secondary winches
- 2 LEWMAR 40 Race manual mainsheet winches
- Swimming ladder
- Rub rail, aluminium

- Helmsman footrests, foldable
- Composite bowsprit with integrated anchor fitting
- Genoa tracks, incl. cars adjustable from cockpit
- German mainsheeet system with adjustable traveller
- 4 deck hatches openable, anchor locker hatch
- 6 deck coach roof windows openable

RIG & SAILS

- Rig, anodized aluminium, keel stepped incl.: dyform rigging, running rigging, kicker, manual jib furler, "Dehler Quick Reefing System", manual backstay tensioner
- QUANTUM AC5 performance sails full battened, triradial, main and jib

NAVIGATION & INSTRUMENTS

- 2 illuminated compasses at steering pedestal
- Navigation lights LED

PROPULSION

- Fuel tank, approx. 160 l
- Engine (Diesel, approx. 29 hp) saildrive, 2 blade folding propeller

FOUIPMENT

- 12 V and 230 V electric system with main panel, 12 V and 230 V socket and 230 V shore power.
- AGM battery set capacity: Starter battery: 1 x 90 Ah, service battery: 1 x 160 Ah
- Country Version: EU / AUS
- Battery charger 35 A
- Manual toilet with sea water flush
- Shower unit in cockpit, warm-/coldwater
- LPG gas system, stowage for 1 bottle
- Manual and electric bilge pump
- Blackwater system (appr. 35 l) with deck extraction and seacock for head
- Fresh water system with electric pump and 20 I hotwater, heated also by main engine
- Fresh water tank, appr. 295 I

SHIPPING & TRANSPORT

- CE Certificate cat. A 6 / B 10 / C 14
- Owners manual
- EC Type Examination Certificate